



Highlights

- Open architecture design works with most tablets (including Android, Windows, and iPad) and Chromebooks with up to 11.6" displays
- Designed to be compatible with a wide variety of manufacturers such as Microsoft, Samsung, Apple, Lenovo, HP, Dell, Amazon, Asus, Acer, and many others
- Smooth sliding door provides easy access to devices and stays within the sleek profile
- Show & Stow™ technology tilting tablet trays make loading and unloading devices simple. Pull trays out to load or unload and they will automatically retract
- Low-profile design protrudes less than 6" (15.2 cm) from the wall saving space
- Quick, simple installation includes mounting template, mounting bracket, and hardware. Mount the bracket on the wall, hang the cabinet and secure with two heavy-duty screws
- Six-point locking bracket keeps devices safe and secure

Designed for

Surface

Ergotron®

Coming soon! Tablet Charging Wall Mount 12



Power up!

This slim storage cabinet is perfect for charging and securing up to 12 tablets and Chromebooks. It's designed to be compatible with a wide variety of manufacturers like Microsoft, Samsung, Apple, Lenovo, HP, Dell, Amazon, Asus, Acer and many others.



Features include a space-saving cabinet profile and easy device access with Show & Stow™ technology.

Compatible with



Windows



SAFETY FOR YOUR STUDENTS AND STAFF

Ergotron not only uses UL-certified components, but goes a step further to have UL certify the entire system to guarantee safe use within the classroom, media center and around the campus. Ergotron products are tested and certified to UL 60950-1 standards, FCC requirements and all applicable country-specific regulations.

Make sure to require this of your device charging solutions. Safe for your devices, your building and your staff.

Certification
UL 60950 Safety of Information Technology Equipment, CAN/CSA C22.2 No. 60950
UL 1667 Tall Institutional Carts for use with Audio, Video and Television Type Equipment
ICES-003 Issue 4, Class A
FCC Part 15 Class A
Country-specific certification as required
RoHS and Reach compliant material used

Windows is a registered trademark of Microsoft Corporation.

© 2012 Google Inc. All rights reserved. Android and Chromebook are trademarks of Google Inc. The Android robot is reproduced or modified from work created and shared by Google and used according to terms described in the Creative Commons 3.0 Attribution License.

- Snap-in tablet tray cable clips make setup simple and keep the device cables perfectly positioned for easy insertion
- Separate AC adapter storage area for easy one-time setup and clean cable storage. Custom country-specific outlet strip includes plenty of space to work with oversized wall adapters and mini-bricks



Tablet Charging Wall Mount 12

Devices	Most tablets and Chromebooks
Charge Method	AC
Screen Size	< 11.6"
# of Devices	12
Slot Size	11.4" x 10.1" x 1.0" 29 x 25,7 x 2,5 cm
Sync Capability	No
UL US LISTED	Full UL 60950 certification
Secure	Locking steel doors
Product Dimensions	26.4"W x 35.6"H x 5.9"D (66,9 x 90,5 x 15,1 cm)
Product Weight	64.5 lb (29,3 kg)
Shipping Dimensions	40.9"W x 28.9"D x 8.4"H (104 x 73,5 x 21,4 cm)
Shipping Weight	77 lb (34,9 kg)
Warranty	5 years workmanship, 2 years power supply, 1 year remaining electrical

- For user and equipment safety, the entire cabinet is tested and certified to UL 60950
- Includes charging and storage cabinet, wall-mounting bracket, mounting hardware for wood stud, concrete and hollow-wall installation, installation template, 6-foot (1,8 m) power cord, key
- Individual device maximum dimensions 11.4" H x 10.1" W x 1.0" D (29 x 25,7 x 2,5 cm) including case and cord
- Individual device maximum weight 3 lbs (1,4 kg). Total rated weight capacity 44.4 lbs (20,1 kg)
- Country-specific 12-receptacle outlet strip is designed to work with oversized wall adapters and mini-sized bricks. AC adapter maximum dimensions 4.1" H x 2.0" W x 4.0" D (10,4 x 5,0 x 10,1 cm)
- Uses the AC adapters that come with each device. AC adapters are not included
- Environmentally clean: RoHS, REACH, WEEE and EU (94/620EC) packaging compliant
- Temperature range:
Operating 0° to 30°C (32° to 86°F)
Storage -40°C to -60°C (-40° to 140°F)
- Relative humidity (maximum):
Operating 10% to 90% (non-condensing)
Storage 5% to 95% (non-condensing)
- Cooling/ventilation: one 12V DC continuous operation fan

Power System	
US/CA/MX	Input: 100-120V~, 12A, 50/60 Hz
EU	Input: 220-240V~, 8A, 50/60 Hz
UK/IE/HK/MY/SG	Input: 220-240V~, 8A, 50/60 Hz
AU/NZ	Input: 220-240V~, 8A, 50/60 Hz
CN	Input: 220-240V~, 8A, 50/60 Hz
JP	Input: 100-120V~, 12A, 50/60 Hz

© 2014 Ergotron, Inc. rev. 01/22/2014/EA Literature made in US
Content is subject to change without notification

Americas Sales and Corporate Headquarters

St. Paul, MN USA
(800) 888-8458
+1-651-681-7600
www.ergotron.com
sales@ergotron.com

EMEA Sales

Amersfoort, The Netherlands
+31 33 45 45 600
www.ergotron.com
info.eu@ergotron.com

APAC Sales

Tokyo, Japan
www.ergotron.com
apaccustomerservice@ergotron.com

Worldwide OEM Sales

www.ergotron.com
info.oem@ergotron.com

