Bluetooth Mobile Keyboard 6000



Version Information		
Product Name	Microsoft® Bluetooth® Mobile Keyboard 6000	
Product Version	Microsoft Bluetooth Mobile Keyboard 6000	
Keyboard Version	Microsoft Bluetooth Mobile Keyboard 6000	
Number Pad Version	Microsoft Bluetooth [®] Number Pad	
Product Dimensions		
Keyboard Length	13.9 inches (355 millimeters)	
Keyboard Width	6.58 inches (167 millimeters)	
Keyboard Depth/Height	0.63 inches (15.9 millimeters)	
Keyboard Weight	14.6 ounces (415 grams) includes 2 AAA alkaline batteries; battery weight	may yary
Number Pad Length	4.02 inches (102 millimeters)	may vary
Number Pad Width	5.29 inches (134 millimeters)	
Number Pad Depth/Height	0.62 inches (15.7 millimeters)	
Number Pad Weight	4.16 ounces (118 grams) includes 1 AAA alkaline battery; typical battery w	eight may vary
Compatibility and Localization		
Interface	Bluetooth® Compatible	
Operating Systems	 Microsoft Windows[®] 7, Windows Vista[®], and Windows XP with Service F Mac OS X v10.4 - 10.5.x 	Pack 2 or higher (excluding Windows XP 64-bit)
Top-line System Requirements	For a Microsoft Windows-based PC:	
Top-line Gystem Requirements	Requires a PC that meets the requirements for and has installed one of these operating systems: • Windows 7, Windows Vista, or Windows XP with Service Pack 2 or higher (excluding Windows XP 64-bit) • Computer enabled with Bluetooth wireless technology For a Macintosh PC: • Mac OS X v10.4 - 10.5.x • Computer enabled with Bluetooth wireless technology	
30 MB of available hard disk space (Install 30 MB) Instance assemble quired for extraor installed.		
0 (1) 111	• Internet access required for software installation	
Compatibility Logos	Compatible with Microsoft Windows 7 Bluetooth logo May logo	
• Mac logo Software Localization For a Microsoft Windows-based PC:		
Software Localization	Microsoft IntelliPoint software may be installed in Simplified Chinese, Traditional Chinese, English, French, German, Italian, Japanese, Korean, Brazilian Portuguese, Iberian Portuguese, or Spanish. If available, standard setup will install the software in the default OS language. Otherwise, the English language version will be installed. For a Macintosh PC: Microsoft IntelliPoint for Mac will install in English, French, German, Italian, Japanese, Brazilian Portuguese, and Spanish. User settings for OS language preference determine which localized version of the software is displayed. In the event that OS language preferences are not supported, the English language version will be displayed.	
Keyboard Localization	Available language sets will vary by product and sales channel. 104 key configuration: Arabic, English (Canada), English (North America), International English (Euro), and International English (ROW) 105 key configuration: English (UK), French (Belgium/Azerty), French (Canada), French (France), German (Germany), German (Switzerland/Luxemburg), Italian, and Norwegian 109 key configuration: Japanese	
Window Technology	100 key comigaration: capanese	
wireless Technology		
Wireless Technology	Blustooth 2.0	
Wireless Platform	Bluetooth 2.0	
Wireless Platform Wireless Frequency	2.4 GHz frequency range	ch as pearly metallic objects and relative positioning of the mouse and receiver
Wireless Platform Wireless Frequency Wireless Range	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, such	ch as nearby metallic objects and relative positioning of the mouse and receiver.
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support	2.4 GHz frequency range	ch as nearby metallic objects and relative positioning of the mouse and receiver.
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID)	ch as nearby metallic objects and relative positioning of the mouse and receiver.
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key	ch as nearby metallic objects and relative positioning of the mouse and receiver.
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key	ch as nearby metallic objects and relative positioning of the mouse and receiver.
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume +	ch as nearby metallic objects and relative positioning of the mouse and receiver.
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume +	ch as nearby metallic objects and relative positioning of the mouse and receiver.
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Life	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key	ch as nearby metallic objects and relative positioning of the mouse and receiver.
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Feite Typing Speed	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume +, and Volume + 500,000 actuations per key 1000 characters per minute	
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Life Typing Speed Storage Temperature & Humidity	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-cor	ndensing)
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Life Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume +, and Volume + 500,000 actuations per key 1000 characters per minute	ndensing)
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Features Media Key Life Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Power Requirements	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-cord	ndensing)
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Life Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-cod 32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-conde	ndensing)
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Features Media Key Life Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Power Requirements	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-cord	ndensing)
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Life Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Power Requirements Battery Type and Quantity	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5.000,000 actuations per key 5.000,000 actuations per key Mute, Volume -, and Volume + 5.000,000 actuations per key 1.000 characters per minute -4.0 °C (-4.0 °C) to 1.40 °F (60 °C) at < 5% to 65% relative humidity (non-conde	ndensing)
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Features Media Key Edutes Media Key Life Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Power Requirements Battery Type and Quantity Battery Life	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-coid of the coid of the	ndensing)
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Life Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Power Requirements Battery Type and Quantity Battery Life Certification Information	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-coi 32 °F (0 °C) to 104 °F (40 °C) at <5% to 80% relative humidity (non-conde Keyboard: 2 AAA alkaline batteries (included) Number Pad: 1 AAA alkaline battery (included) Keyboard: 10 months typical Number Pad: 5 months typical	ndensing)
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Hot Key Life Media Key Features Media Key Features Media Key Jife Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Power Requirements Battery Type and Quantity Battery Life Certification Information Country of Manufacture	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-cord 32 °F (0 °C) to 140 °F (60 °C) at < 5% to 80% relative humidity (non-cord Keyboard: 2 AAA alkaline batteries (included) Number Pad: 1 AAA alkaline battery (included) Keyboard: 10 months typical Number Pad: 5 months typical People's Republic of China (PRC)	ndensing)
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Hot Key Life Media Key Features Media Key Features Media Key Life Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Power Requirements Battery Type and Quantity Battery Life Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-coil 32 °F (0 °C) to 140 °F (40 °C) at <5% to 80% relative humidity (non-coil 32 °F (0 °C) to 144 °F (40 °C) at <5% to 80% relative humidity (non-coil Keyboard: 2 AAA alkaline batteries (included) Number Pad: 1 AAA alkaline battery (included) Keyboard: 10 months typical People's Republic of China (PRC) Yes	ndensing)
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Features Media Key Features Media Key Jife Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Power Requirements Battery Type and Quantity Battery Life Certification Information Country of Manufacture	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-coid) 32 °F (0 °C) to 140 °F (40 °C) at < 5% to 80% relative humidity (non-coid) Keyboard: 2 AAA alkaline batteries (included) Number Pad: 1 AAA alkaline batteries (included) Keyboard: 10 months typical Number Pad: 5 months typical People's Republic of China (PRC) Yes Yes This device complies with all applicable worldwide regulations and restricti Use of Certain Hazardous Substances in Electrical and Electronic Equipm	ndensing)
Wireless Platform Wireless Frequency Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Features Media Key Life Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Power Requirements Battery Type and Quantity Battery Life Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5.000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at <5% to 65% relative humidity (non-coid) 32 °F (0 °C) to 104 °F (60 °C) at <5% to 80% relative humidity (non-coid) Keyboard: 2 AAA alkaline batteries (included) Number Pad: 1 AAA alkaline batteries (included) Keyboard: 10 months typical Number Pad: 5 months typical People's Republic of China (PRC) Yes This device complies with all applicable worldwide regulations and restricti Use of Certain Hazardous Substances in Electrical and Electronic Equipm regulation regarding Substances of Very High Concern. This Class B digital apparatus complies with Part 15 of the U.S. Federal C Operation is subject to the following two conditions: (1) this device may no including interference that may cause undesired operation. Tested to comy office use. The term "IC:" before the certification/registration number only services.	ons including, but not limited to: EU directive 2002/95/EC on the Restriction of the ent and EU Registration Evaluation and Authorization of Chemicals (REACH) ommunications Commission (FCC) rules, Canadian ICES-003, and RSS-210. It cause interference, and (2) this device must accept any interference received, bly with FCC (U.S. Federal Communications Commission) Standards. For home or signifies that the Industry Canada technical specifications were met. Model numbers:
Wireless Platform Wireless Frequency Wireless Range Bluetooth Profile Support Product Feature Performance QWERTY Key Life Hot Key Life Media Key Features Media Key Features Media Key Jife Typing Speed Storage Temperature & Humidity Operating Temperature & Humidity Power Requirements Battery Type and Quantity Battery Life Certification Information Country of Manufacture ISO 9001 Qualified Manufacturer ISO 14001 Qualified Manufacturer Restriction on Hazardous Substances	2.4 GHz frequency range 10 meters (33 feet) typical. Note: RF range is affected by many factors, sur Human Interface Device (HID) 5,000,000 actuations per key 500,000 actuations per key Mute, Volume -, and Volume + 500,000 actuations per key 1000 characters per minute -40 °F (-40 °C) to 140 °F (60 °C) at < 5% to 65% relative humidity (non-cord of the control of the contro	ons including, but not limited to: EU directive 2002/95/EC on the Restriction of the ent and EU Registration Evaluation and Authorization of Chemicals (REACH) ommunications Commission (FCC) rules, Canadian ICES-003, and RSS-210. It cause interference, and (2) this device must accept any interference received, bly with FCC (U.S. Federal Communications Commission) Standards. For home or signifies that the Industry Canada technical specifications were met. Model numbers: