

TASK LIGHTING

VERANO



SEE YOUR WORK IN A PLEASING LIGHT

Verano brings the warmth and brightness of natural daylight to the desktop. Verano's high CRI and neutral color temperature will put your work in the best possible light.

Verano's unique mounting system allows you to rotate or slide the fixture as desired for glare-free performance. Plus, project managers will appreciate Verano's lightning fast install, LEED credit eligibility and the ability to daisy chain up to four units from a single transformer.

Eco and user friendly, Verano is a natural choice.





Available in 24", 36" & 48"
lengths with an ultra slim 1"
profile in three standard colors.

LET WORK
COME TO LIFE™

Workrite
ergonomics®


TASK LIGHTING
VERANO™



Ultra-slim profile slips discretely under cabinets and illuminates with vivid, quality light.



Mounts with magnets on metal or screws on wood and can daisy chain up to four units.



Fixture rotates +/- 30° to direct light where needed and reduce glare.

Features:

- Three lengths: 24", 36", 48" (nominal)
- Ultra-slim 1" x 3/4" profile
- Fixture rotates +/-30°
- Available in 3 colors: Winter, Sterling and Carbon
- Custom colors available with no upcharge, 200 minimum quantity
- Magnetic rotating and fixed mounts and wood shelf rotating and fixed mounts included for rapid install
- Push button power switch
- Cord clips included
- Meets DOE Ergonomics Guidelines and IESNA RP-1-04 section 2.3 requirements for task lighting illuminance levels
- Specify 24" or 48" jumper cord for all daisy chain units
- Color temperature: 3500K, CRI:92
- 50,000 hour lifetime LEDs
- UL listed, cUL listed
- 10 year warranty on fixture

Wiring & electrical:

- LED Wattage: 24" 9.8W, 36" 12.9W, 48" 18.4W
- Can daisy chain up to 9 ft. of nominal fixture length
- Specify 24" or 48" jumper cord for add-on jumper units
- All Daisy Chains must use 48W (4A) transformers

Environmental considerations

- Post-consumer recycled content used in packaging; aluminum housing all recyclable at end of life
- Finish is VOC free water-based paint
- LEED credit eligibility
 - Energy and atmosphere, credit 1.1 (1-3 points)
 - Optimize energy performance: lighting power
 - Innovation in design, credit 1.1-1.4 (1-4 points)
 - Implementation of comprehensive ergonomic program

Configuration	Fixture Length	Model #	Color ⁽³⁾	Transformer Size	Weight
Standalone	24"	VER-24-	□	24W ⁽¹⁾	2
	36"	VER-36-	□	24W ⁽¹⁾	3
	48"	VER-48-	□	24W ⁽¹⁾	4

Daisy Chain Parent	24"	VER-24-P-	□	48W ⁽²⁾	2
	36"	VER-36-P-	□	48W ⁽²⁾	3
	48"	VER-48-P-	□	48W ⁽²⁾	4

Configuration	Fixture Length	Model #	Cord Length ⁽⁴⁾	Color ⁽³⁾	Weight
Daisy Chain Jumper	24"	VER-24-J -	□ -	□	2
	36"	VER-36-J -	□ -	□	3
	48"	VER-48-J -	□ -	□	4

(1) 24W transformer: 12V, 2A, Class 2, 2"W x 3 1/4"H x 1 1/2"D transformer, 2 prong plug on 10' cord with barrel connector plug to fixture. **Available from January 2013.**

(2) 48W transformer: 12V, 4A, Class 2, 4 5/8"W x 2 1/2"H x 1 1/2"D transformer, 2 prong plug on 5' cord connects to 54" cord with barrel connector plug to fixture.

(3) Colors: **[W]**-Winter, **[S]**-Sterling, **[C]**-Carbon

(4) Daisy Chain Cord Lengths: **[2,4]**-24", **[4,8]**-48"

Mixed Chain Configurations

Number of fixtures within same chain

VER-24	VER-36	VER-48	Total per Chain	
1	1		2	Listed to left are all possible configurations of mixed size fixtures within a single daisy chain. Refer to the chart below under 'Specifications' for maximum number of the same sized fixtures per daisy chain.
1		1	2	
	1	1	2	
1	2		3	
2	1		3	
2		1	3	
1	1	1	3	


Photometrics

Source at 18"


inches	18	12	6	0	6	12	18
12	5	14	25	26	24	18	7
6	23	85	89	110	104	68	33
0	37	88	134	158	143	102	53
6	29	83	128	158	142	95	44
12	10	36	66	81	73	51	23

Model # tested: VER-36, average illuminance: 74 footcandles

Specifications: Lengths




Actual Length	Compatible Shelf Width	LED Wattage	Number of LEDs	Max. per Chain
19 1/4"	24"	9.8 W	8	4
27 3/8"	36"	12.9 W	12	3
35 3/8"	48"	18.4 W	16	2



* Fixed, non-rotating kit included as standard

Actual Size (rotating mount)



Workrite Ergonomics, Inc. 2277 Pine View Way, Suite 100, Petaluma, CA 94954
www.workriteergo.com 800.959.9675

©2012 Workrite Ergonomics | All referenced company and product names are trademarks, registered trademarks or copyrights of their respective holders.

1400225-1112 Subject to change without notice.

Workrite
ergonomics®