

Highlights

- Flexible, open-architecture design is scalable for future computer equipment upgrades
- Comfortable, ergonomic data entry work sitting or standing with ergonomic 20" (51 cm) lift adjustment
- Five-inch (13 cm) LCD height adjustment ergonomically accommodates average range of users
- Extremely easy-to-clean design promotes infection control
- Barcode scanner holder provides easy access to hand-held scanner
- Extends/retracts LCD and keyboard up to 39" (99 cm); fold equipment back out of the way when not in use. With the keyboard folded up, total system depth is as little as 12" (30.5 cm)
- Ergonomic negative-tilt keyboard tray with left or right mouse tray ensures wrists remain in a neutral position during data entry
- Maintains the relative position of screen and keyboard throughout full range of motion
- Clean, concealed and neat routing of cables through the expansive cable management system

Ergotron[®]

StyleView[®] HD Combo



Wall-mount workstation with single-motion adjustment

Provides sit-to-stand vertical adjustment and articulation that maximizes patient-caregiver interaction. Maintains the relative position of the screen throughout the full range of motion. Keyboard tray extends up to 39" (99 cm) and folds up 90° for total clearance of approximately 12" (30.5 cm). Optional 18" (46 cm) extender arm increases range of motion for even greater reach.



870-05-089-EA www.ergotron.com © 2009 Ergotron, Inc. All rights reserved



- ① Integrated keyboard tray with right/left mouse tray
- O Fold-down keyboard tray with built-in mouse pad surface
- 3 Adjustable negative-tilt keyboard tray (0° to -10°)
- \circledast Integrated mouse and barcode scanner holders provide easy access
- ⑤ Optional 18" (46 cm) extender arm (45-219-216 or 45-219-200) increases range of motion for even greater reach
- Betented CF lift-and-pivot motion technology provides premium 5" (13 cm) LCD height adjustment, portrait-to-landscape rotation and 30° tilt
- ⑦ Durable, easy-to-clean exterior composed of aluminum, high-grade plastic and powdercoated painted steel

		LB kg		\bigcirc		\bigcirc	
L	CD Size	Weight Capacity*	Lift**	Tilt	Pan	Rotation	VESA
	24″	see below	20″ 51 cm	30°	180°	90°	MIS-D

* Weight Capacity: display = 6–18 lbs (2.7–8.2 kg); keyboard, mouse and barcode scanner = 5 lbs (2.3 kg) **Lift Range: LCD and keyboard adjusts 15" (38 cm) in tandem; LCD adjusts 5" (13 cm) independently; maximum LCD height adjustment = 20" (51 cm)

Product Name	StyleView HD Combo		
Part Numbers	45-215-216 (white) 45-215-200 (black)		
Product Includes	HD Combo Arm, wall mount bracket, height- adjustable LCD mount, wrist rest, scanner and mouse holder, integrated keyboard tray with left/ right mouse tray, handle, manual, VESA-monitor mounting kit, cable ties		
Shipping Dimensions	12"H x 20"W x 24"D (305 x 508 x 610 mm)		
Shipping Weight	25 lbs (11.3 kg)		
Warranty	5 years		
Weight Capacity*	Display = 6–18 lbs (2.7–8.2 kg); keyboard, mouse and barcode scanner = 5 lbs (2.3 kg)		
Compatible Display(s)	Almost any VESA compliant monitor up to 24" VESA FDMI, MIS-D, 75/100, C (hole patterns = 100 x 100 mm and 75 x 75 mm)		

⑧ Clean, concealed and neat routing of cables through the expansive cable management system

4



Stends/retracts LCD and keyboard up to 39" (99 cm); fold equipment back out of the way when not in use. With the keyboard folded up, total system depth is as little as 12" (30.5 cm)

6



Product Name	StyleView HD Combo System
Part Numbers	45-216-216 (white) 45-216-200 (black)
Product Name	StyleView HD Extender
Part Numbers	45-219-216 (white) 45-219-200 (black)

 $\textcircled{\sc 0} 2009 \ \mbox{Ergotron, Inc.} \ \ \mbox{rev. 04/24/2009} \ \ \ \mbox{870-05-089-EA} \ \ \ \mbox{Content is subject to change without notification}$

Americas Sales and Corporate Headquarters	EMEA Sales
St. Paul, MN USA (800) 888-8458	Amersfoort, The Netherla +31 33 45 45 600
+1-651-681-7600 www.ergotron.com sales@ergotron.com	www.ergotron.com info.eu@ergotron.com

lands Tokyo, Japan www.ergotron.com info.apac@ergotron.com

APAC Sales

Worldwide OEM Sales

www.ergotron.com info.oem@ergotron.com

