

INSTALLATION INSTRUCTIONS

MSB-6243

DISPLAY MOUNTING INTERFACE^{UL}

Prior to assembly, unpack carton completely and verify contents.

If you are missing any of the following components, please contact Customer Service at 1-800/582-6480




Figure 1

(4) Mounting Buttons – Black Zinc

(4) M8 x 25 Phillips Head Cap Screw

(4) M8 x 35 Phillips Head Cap Screw

BEFORE PROCEEDING, READ INSTALLATION INSTRUCTIONS COMPLETELY

CAUTION!

DISPLAYS ARE EXTREMELY FRAGILE.

WARNING!

ALL COMPONENTS MUST BE SECURELY FASTENED TO A STRUCTURAL MEMBER CAPABLE OF SUPPORTING 4 TIMES THE COMBINED WEIGHT OF ALL COMPONENTS PLUS THE EQUIPMENT BEING MOUNTED. IF IT CANNOT SUPPORT THIS WEIGHT, THE STRUCTURE MUST BE REINFORCED.

THE MAXIMUM WEIGHT TO BE INSTALLED ON THE INTERFACE IS 125 POUNDS (56.69 KG).

1. If applicable, remove rubber caps over mounting holes before attempting to attach buttons using four M8 screws provided (see Figure 2 & Figure 3).
2. Attach mounting buttons to display using correct length screws depending on screen (see Figure 2 & Figure 3).
3. With the aid of another person, lift the display up to the Chief Mount and align buttons of mounting bracket with slots on the Chief Mount.
4. Raise safety latch on the Chief Mount to secure the display, making sure latch is completely engaged.




Figure 2




Figure 3