


# SNAP ON CHARGING CAP

## Installation Instructions

---



**CHG-CAP**

---

## IMPORTANT SAFETY INSTRUCTIONS

### WARNING

- Keep away from extreme heat, direct sunlight, humidity and moisture
- Avoid extreme high or low ambient temperatures and sudden temperature changes
- Keep away from children
- Disconnect from power before cleaning
- Never operate this furnishing if it has a damaged cord or plug
- DO NOT use if wet or damaged
- DO NOT open, modify or repair
- DO NOT use outdoors

### REGULATORY COMPLIANCES

This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions:

- (1) This device may not cause harmful interference, and
- (2) this device must accept any interference received, including interference that may cause undesired operation.


This device complies with CAN ICES-5(B)/NMB-5(B)

This device conforms to UL STD. 62368-1 and certified to CSA STD C22.2 NO. 62368-1



---

## SPECIFICATIONS



### Power Supply

Input: 100-240VAC, 50/60Hz, 2.0A (Max.)

Output: 24VDC, 3A, 72W

### USB Hub

Output:

Type C: 5V/3A, 9V/3A, 12V/3A, 15V/3A, 20V/3A, PD compatible 65W max

Type A1: 5V/3A, 9V/2A, 12V/1.5A, QC 3.0 compatible 18W max

Type A2: 5V/3A, 9V/2A, 12V/1.5A, QC 3.0 compatible 18W max

Type C + Type A1: 45W+18W, Max. 63W

Type C + Type A2: 45W+18W, Max. 63W

### Limitations:

USB Hub supports charging only, no data transfer

When PD device connected to USB-C port, only one USB-A port works at QC 3.0

When USB-C is not under the load, both USB-A ports work at QC 3.0

Operating temperature: 0 °C - 40 °C, 5% -90% RH

1

