



# REYA POWER

ACCESSORIES



HAT  
DESIGN WORKS™  
HUMAN ACTIVE TECHNOLOGY


# SMART. BEAUTIFUL. POWERFUL.

Meet Reya - our new power family. Reya's design-forward architecture with soft, curved lines offers a full spectrum of mountable power options for your workstation. Whatever your power needs, big or small, Reya provides power conveniently at your fingertips.



## LOW PROFILE USB HUB\*

### Finishes



### Features

- 1 USB-A charger port
- 1 USB-C charger port
- Can charge laptop up to 65 Watts
- Mount: Desk edge/surface mount, under mount, edge mount (Desk edge/surface mount: 0.5" - 1.75")

### Specifications

- Input: DC, 65W max from HAT Base Control Box
- Output:
  - Single Port In Use:
    - USB-C: QC2.0, QC3.0, PD3.0, PPS, 65W max
    - USB-A: 5V/2A, 10W max
  - Both Ports In Use:
    - USB-C: 20V2.25A max
    - USB-A: 5V2A max

### Dimensions

- Product: 2.4" x 2.2" x 1.2"
- Cord Length: 5'

### Part Numbers


PWR-AC-\_\_

\* Compatible with HAT bases only



## STANDARD SURFACE POWER MODULE

### Finishes



### Features

- 2 power receptacles
- 1 USB-A charger port
- 2 USB-C charger ports
- Can charge laptop up to 65 Watts
- Mount: Desk edge, 0.75" - 1.75"
- Conforms and tested to UL 962A and UL 1310 standards
- Tamper-resistant (TR) AC outlets
- Integrated circuit breaker

### Specifications

- Input: 125VAC, 60Hz, 15A max
- Output:
  - AC Outlets (2): 120VAC, 60HZ, 15A max
  - Single port use:
    - USB-A: 5V3A, 9V2.A, 12V1.5, 18W max
    - USB-C1: 5V/3A, 9V3A, 12V3A, 15V3A, 20V3.25A; PPS (3.3-11V4.05A, 3.3-16V3A, 65W max); PD3.0, APPLE2.4A, DCP1.5A, QC2.0/3.0, AFC
    - USB-C2: 5V3A, 9V2.22A, 12V1.67A, 20W max
  - Multi port use:
    - USB-C1 + USB-C2: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 max 20W (5V3A, 9V2.22A, 12V1.67A)
    - USB-C1 + USB-A: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-A max 18W (5V3A, 9V2.A, 12V1.5, 18W max)
    - USB-C2 + USB-A: Both share 15W
    - USB-C1 + USB-C2 + USB-A: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 & USB-A share 15W

### Dimensions

- Product: 7.1" x 3.3" x 2.3"
- Cord Length: 6'


### Part Numbers

PWR-ACC-\_\_



## WIRELESS SURFACE POWER MODULE

### Finishes



### Features

- 2 power receptacles
- 1 USB-A charger port
- 2 USB-C charger ports
- Can charge laptop up to 65 Watts
- Fast Qi certified wireless charging
- Mount: Desk edge, 0.75" - 1.75"
- Conforms and tested to UL 962A and UL 1310 standards
- Tamper-resistant (TR) AC outlets
- Integrated circuit breaker

### Specifications

- Input: 125VAC, 60Hz, 15A max
- Output:
  - AC Outlets (2): 120VAC, 60HZ, 15A max
  - Single port use:
    - USB-A: 5V3A, 9V2.A, 12V1.5, 18W max
    - USB-C1: 5V/3A, 9V3A, 12V3A, 15V3A, 20V3.25A; PPS (3.3-11V4.05A, 3.3-16V3A, 65W max), PD3.0, APPLE2.4A, DCP1.5A, QC2.0/3.0, AFC
    - USB-C2: 5V3A, 9V2.22A, 12V1.67A, 20W max
  - Multi port use:
    - USB-C1 + USB-C2: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 max 20W (5V3A, 9V2.22A, 12V1.67A);
    - USB-C1 + USB-A : USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-A max 18W (5V3A, 9V2.A, 12V1.5, 18W max)
    - USB-C2 + USB-A : Both share 15W
    - USB-C1 + USB-C2 + USB-A : USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 & USB-A share 15W;
    - Wireless Charging: Qi 5W, 7.5W, 10W, 15W (auto detection);

### Dimensions

- Product: 7.1" x 3.3" x 2.4"
- Cord Length: 6'

### Part Numbers

PWR-ACC-WRLS-\_\_



**POWER STRIP**

**Finishes**

- White  
WH
- Black  
BK

**Features**

- 6 power receptacles
- Conforms and tested to UL 962A and UL 498 standards
- Tamper-resistant (TR) AC outlets
- Integrated circuit breaker

**Specifications**

- Input: 125VAC, 60Hz, 15A max
- Output:
- AC Outlets (6): 120VAC, 60HZ, 15A max

**Dimensions**

- Product: 14.6" x 2.4" x 1.5"
- Cord Length: 6'

**Part Numbers**

PWR-STRP-\_\_



**POWER STRIP WITH HARDWIRED STANDARD SURFACE POWER MODULE**

**Finishes**

- White  
WH
- Black  
BK

**Features**

- Power Strip: 6 power receptacles
- Power Module: 2 power receptacles
- 1 USB-A charger port
- 2 USB-C charger ports
- Can charge laptop up to 65 Watts

- Conforms and tested to UL 962A, UL 1310, and UL 498 standards
- Tamper-resistant (TR) AC outlets
- Integrated circuit breaker

**Specifications**

- Input: 125VAC, 60Hz, 15A max
- Output, Power Strip:
- AC Outlets (6): 120VAC, 60HZ, 12A max
- Output, Surface Mounted Power Module:
- AC Outlets (2): 120VAC, 60HZ, 15A max
- USB:
- Single Port Use
- USB-A: 5V3A, 9V2.A, 12V1.5, 18W max
- USB-C1: 5V/3A, 9V3A, 12V3A, 15V3A, 20V3.25A; PPS (3.3-11V4.05A, 3.3-16V3A, 65W max), PD3.0, APPLE2.4A, DCP1.5A, QC2.0/3.0, AFC
- USB-C2: 5V3A, 9V2.22A, 12V1.67A, 20W max
- Multi Port Use
- USB-C1 + USB-C2: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 max 20W (5V3A, 9V2.22A, 12V1.67A)
- USB-C1 + USB-A: USB-C1 max 45W (5V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-A max 18W (5V3A, 9V2.A, 12V1.5, 18W max)
- USB-C2 + USB-A: Both share 15W
- USB-C1 + USB-C2 + USB-A : USB-C1 max 45W (5V3A, 9V3A, 9V3A, 12V3A, 15V2.67A, 20V2.25A); USB-C2 & USB-A share 15W

**Dimensions**

- Surface Unit: 7.1" x 3.3" x 2.4"
- Power Strip: 14.6" x 2.4" x 1.5"
- Cord Length:
- Input: 6'
- Between Units: 3'

**Part Numbers**

PWR-ACC-STRP-\_\_