





27"
MAX

2.2-22lbs
RATED

Human Active Technology
800 524 2744
customerservice@team-hat.com
team-hat.com

PARTS LIST


A Dual Top Down Mount 1x
8540




B 6-inch Post 2x
415981




C M8-1.25 x 100mm SHCS 2x
716368



D 9-inch Beam Assembly 2x
416088




E Dog Washer 2x
105189




F 10-32 x 3/8" FPhMS w/Lock Patch 2x
705198




G Quick Connect VESA Plate 2x
114808



H M4 x 12mm Phillips Pan Head Screw 8x
701153




I Cable Management Clip 2x
116025




J 3/32" Allen Wrench 1x
700146




K 6mm Allen Wrench 1x
717654




L 4mm Allen Wrench 1x
709877



M* M8 x 140mm SHCS 1x
716280



N* Spacer 1x
701544




O* Lock Nut 1x
710015




DESK CLAMP CONFIGURATION

1





Desk thickness
up to 1.5" (3.8 cm)



Desk thickness
up to 1.5" (3.8 cm)



OR



2




Tighten to
60 in-lbs
minimum





THRU-DESK CONFIGURATION*


3





4













2x

2x

2x








⌚ Adjust clockwise (up to 1 full turn),
for maximum load.

⌚ Adjust counterclockwise (up to 1 full turn),
for minimum load.



Damage may result,
due to overtightening.

