


Installation and Assembly - Adapter Bracket for VESA® 400 x 300 Screens

Model: PLP-V4X3

IMPORTANT! Read instruction sheet before you start installation and assembly. *Before you start make sure all parts listed are included with your product. Some parts may appear slightly different than illustrated.*

Parts List

Description	Qty.	Part #
AA adapter plate	1	201-1743
BB M5 x 10 mm socket pin screw	4	520-1063
CC M6 x 16 mm socket pin screw	4	520-1132
DD 4 mm allen wrench	1	560-9646
EE M8 x 40 mm screw	4	520-1152
FF multi-washer	4	580-1036
GG .5 I.D. spacer	4	590-1121
HH washer	4	540-9406
II .34 I.D. spacer	4	540-1002



⚠ WARNING

•Do not overtighten, or permanent damage may occur to the screen. Torque to 26-35 in • lb (30-40 kg • cm).

- 1 Attach adapter bracket (**AA**) to back of screen using four screws (**EE**) with washers (**HH**) as shown in figure 1, or four screws (**BB** or **CC**) with washers (**FF**) as shown in figure 2. Tighten screws using 4 mm allen wrench (**DD**). For screens with a bump out, recess or shallow inserts, spacers (**GG** and/or **II**) may be used between the adapter bracket and your screen as shown in detail 1.

