



PRODUCT SPECIFICATIONS SHEET

MODEL: TRULY.™ TY608 TASK CHAIR



IMAGE ABOVE SHOWN WITH OPTIONAL JR-69 ARMS (AT
ADDITIONAL COST)

OVERALL DIMENSIONS (APPROX.)

Overall height	38.25" - 47.5"
Overall width	27"
Seat height	17" - 22"
Seat width	20.75"
Seat depth	17.5" - 20.6"
Back width	20"
Back height	24"
Warranty coverage	Lifetime Limited Meets/exceeds ANSI/ BIFMA standards

KEY COMPONENTS

Mechanism	Stamped steel, dual housing w/ 2:1 backrest to seat tilt ratio. Synchronized knee tilt control with lockout at the upright position. Center-mounted coil spring tension at front of control, & tilt adjustment range of approximately 8° on the seat, 16° on the backrest.
Seat slider	3.1" smooth travel range, double-spring activated. Uses dual, stamped steel plates & a self-lubricating slider with 7 discreet position stops.
Back membrane	Next generation polymer blend with variable thickness, slats/bridges & other detailing to provide flexibility & support for users.
Back shroud	Extra-strong nylon with fiberglass reinforcement.
Back yoke	Black powdercoated, formed aluminum yoke serves to provide rigidity and support to balance out pliable back membrane.
Seat foam	3 lbs. density high-resilience polyurethane foam that is molded for minimal scrap waste. Compound-curved with a mild contours for optimal cushioning comfort.
Seat wood	8-layer heavy-duty, cross-grained plywood with compound curves. Made from FSC- & CARB-Certified, tree-farm harvested wood.
Cylinder	121mm stroke, premium pneumatic cylinder (350 newtons). Black-oxide housing & piston finish to lessen visibility of smudges & dirt.
Base	27" tip-to-tip diameter, black powdercoated aluminum, 5-star base with fiberglass-fill & patented stepped hub design for extra strength & long-term stability.
Caster	55mm diameter, black hoodless ultra-utility casters. Constructed of polyurethane tread & black high impact resistant thermoplastic housing.